


- Vibration absorber under the frame
- Crank case heater
- Vibration absorber on compressor discharge line
- Liquid receiver
- Liquid line filter dryer
- Solenoid valve
- Sight glass
- LP presostat
- HP presostat
- HP/LP Gauges
- Electrostatic powder paint case
- Acoustic insulation
- Axial fan
- Condenser fan speed controller
- Electrical board



Design A



Design B



Design C

| NORMAL TEMPERATURE (ΣΥΝΤΗΡΗΣΗ) | | | | | | | | |
|--------------------------------|------------------------------|------------|--------------------------|---------------------|------------------------------|---------------------------------|---------------------|-------------------|
| | No. of compressors and model | HP nominal | Refrigeration power (kW) | Absorbed power (kW) | Sound pressure Lp 10mt dB(A) | No. of Fans & Fan Diameter (mm) | Design & LxWxH (mm) | Voltage (V-Ph-Hz) |
| EMBRACO | 1 x NT6220GK | 0,75 | 0,95 | 0,66 | 27 | 1 x 300 | A 875x370x500 | 230-1-50 |
| | 1 x NEU6215GK | 0,75 | 0,96 | 0,67 | 27 | 1 x 300 | A 875x370x500 | 230-1-50 |
| | 1 x NT6226GK | 1 | 1,14 | 0,79 | 27 | 1 x 300 | A 875x370x500 | 230-1-50 |
| | 1 x NJ9232GK | 1,3 | 1,68 | 1,06 | 32 | 1 x 350 | A 875x370x550 | 230-1-50 |
| | 1 x NJ9238GK | 1,5 | 2,14 | 1,36 | 32 | 1 x 350 | A 925x340x550 | 230-1-50 |
| | 1 x NJX6250GS | 2 | 2,82 | 1,88 | 37 | 1 x 400 | A 925x340x600 | 400-3-50 |
| COPELAND | 1 x ZB15KCE-TFD | 1,5 | 3,11 | 2,06 | 37 | 1 x 400 | A 925x340x600 | 400-3-50 |
| | 1 x ZB19KCE-TFD | 2 | 3,63 | 2,21 | 37 | 1 x 400 | A 925x340x600 | 400-3-50 |
| | 1 x ZB21KCE-TFD | 3 | 4,68 | 2,80 | 37 | 1 x 400 | A 1175x340x600 | 400-3-50 |
| | 1 x ZB26KCE-TFD | 3,5 | 5,33 | 3,14 | 41 | 1 x 450 | A 1175x340x650 | 400-3-50 |
| | 1 x ZB30KCE-TFD | 4 | 6,44 | 3,67 | 40 | 1 x 500 | A 1175x340x700 | 400-3-50 |
| | 1 x ZB38KCE-TFD | 5 | 8,04 | 4,58 | 40 | 2 x 400 | B 1225x340x1100 | 400-3-50 |
| | 1 x ZB45KCE-TFD | 6 | 9,41 | 5,19 | 43 | 2 x 500 | B 1225x340x1300 | 400-3-50 |
| | 1 x ZB48KCE-TFD | 7 | 10,80 | 6,02 | 43 | 2 x 500 | B 1225x340x1300 | 400-3-50 |
| | 1 x ZB58KCE-TFD | 7,5 | 11,95 | 6,90 | 43 | 2 x 500 | B 1225x340x1300 | 400-3-50 |
| | 1 x ZB66K5E-TFD | 9 | 14,00 | 7,65 | 43 | 2 x 500 | B 1375x400x1300 | 400-3-50 |
| | 1 x ZB76KCE-TFD | 10 | 16,15 | 8,88 | 43 | 2 x 500 | B 1375x400x1300 | 400-3-50 |
| | 1 x ZB95KCE-TFD | 12 | 19,35 | 11,65 | 46 | 4 x 500 | C 2250x510x1300 | 400-3-50 |
| | 1 x ZB114K5E-TFD | 15 | 24,00 | 14,40 | 46 | 4 x 500 | C 2250x560x1300 | 400-3-50 |

| LOW TEMPERATURE (ΚΑΤΑΨΥΞΗ) | | | | | | | | |
|----------------------------|------------------------------|------------|--------------------------|---------------------|------------------------------|---------------------------------|---------------------|-------------------|
| | No. of compressors and model | HP nominal | Refrigeration power (kW) | Absorbed power (kW) | Sound pressure Lp 10mf dB(A) | No. of Fans & Fan Diameter (mm) | Design & LxWxH (mm) | Voltage (V-Ph Hz) |
| COPELAND | 1 x ZF09K4E-TFD | 3 | 1,56 | 1,94 | 37 | 1 x 400 | A 925x340x600 | 400-3-50 |
| | 1 x ZF11K4E-TFD | 3,5 | 1,92 | 2,65 | 37 | 1 x 400 | A 1175x340x600 | 400-3-50 |
| | 1 x ZF13K4E-TFD | 4 | 2,23 | 2,85 | 40 | 1 x 450 | A 1175x340x600 | 400-3-50 |
| | 1 x ZF15K4E-TFD | 5 | 2,72 | 3,87 | 40 | 1 x 500 | A 1175x340x700 | 400-3-50 |
| | 1 x ZF18K4E-TFD | 6 | 3,21 | 5,50 | 40 | 1 x 500 | A 1175x340x700 | 400-3-50 |
| | 1 x ZF25K5E-TFD | 7,5 | 4,25 | 5,08 | 44 | 2 x 450 | B 1225x340x1200 | 400-3-50 |
| | 1 x ZF41K5E-TFD | 13 | 6,85 | 7,66 | 43 | 2 x 500 | B 1375x400x1300 | 400-3-50 |
| | 1 x ZF49K5E-TFD | 15 | 8,31 | 10,35 | 43 | 2 x 500 | B 1375x400x1300 | 400-3-50 |

References / Important notes

FROST-IT S.A. reserves the right to make any changes or technical modifications to its products without any notification.